



## **ECONOMICAL PRESSURE SWITCH**

Vacuum and Compound Ranges Available, Adjustable Set Point



3.625 [92.08] 1/4 NP

2.375 [60.33]

SERIES A1PS/A1VS Economical Pressure Switches are designed with a 15 Amp SPDT switch for direct control of pumps and motors. Available in pressure, vacuum, or compound ranges, the switches offer a field adjustable set point. Easily adjust the switch by aligning the top of the self locking adjusting nut with the desired setting indicated on the adjacent range scale. Connection is 1/4" male NPT for quick installation and can be mounted in any position.

## FEATURES/BENEFITS

- 15 A contact allows direct control reducing costs and reliability by having to introduce additional contacts and relavs
- Field adjustable reduces installation time bring application on-line faster

## APPLICATIONS

OEM

Compressors

Motor control

Process equipment
 Pump control

## **SPECIFICATIONS**

Service: Compatible liquids or gases. Wetted Materials: Diaphragm: Buna-N: Body with fitting: Zinc alloy, chromate finish.

Temperature Limits: -31 to 185°F (-35 to 85°C).

Pressure Limits: 600 psig.

Vacuum Limits: 29.9" Ha (vacuum and compound models only).

Switch Type: SPDT snap action.

screw cap. Cycling: Not to exceed 1 Hz. Sensor Element: Diaphragm.

terminals.

Weight: 7.4 oz (209 g).

Electrical Ratings: 15 A (resistive) @

250 VAC, 1/2 HP @ 250 VAC.

Electrical Connections: Three screw

Process Connection: 1/4" male NPT.

Set Point: Field adjustable via knurled

Agency Approvals: UL.

MODEL CHART							
	Set Point Range	Repeatability	Deadband		Set Point Range	Repeatability	Deadband
Model	(kPa)	(kPa)	(approx.) (kPa)	Model	(kPa)	(kPa)	(approx.) (kPa)
A1PS-14	1.5 to 3.5 psi (10 to 24)	±0.15 psi (1)	0.5 to 1.7 psi (3 to 11)	A1VS-14	6-28" Hg (-20 to -94)	±1.2" Hg (-4)	3-14" Hg (-10 to -47)
				A1VS-24	28" Hg to 3.5 psig (-94 to 24)		6" Hg - 1.5 psi (-20 to 10)
	30 to 150 psi (207 to 1034)		5 to 30 psi (34 to 207)			±0.15 psi (1)	
A1PS-44	100 to 500 psi (689 to 3445)	±20.0 psi (138)	30 to 120 psi (207 to 827)				