


DIGITAL TEMPERATURE SWITCH PROBES & ACCESSORIES

Probes to Be Used with TS2, TSS2, TSWB, TSW, TS3, TSX3, and 40M



Scan here to watch product video

MODEL CHART - SENSORS			
Model	Sensor	Cap Material	Length ft (m)
TS-1	PTC	Brass	5 (1.5)
TS-11	PTC	Brass	10 (3)
TS-2	PTC	Stainless steel	5 (1.5)
TS-21	PTC	Stainless steel	10 (3)
TS-5	PTC	PVC	5 (1.5)
TS-51	PTC	PVC	10 (3)
TS-6	PTC	Polyamide resin coated brass	5 (1.5)
TS-61	PTC	Polyamide resin coated brass	10 (3)
TS-7	NTC	None	5 (1.5)
TS-71	NTC	None	10 (3)
TS-8T	NTC	Stainless steel	5 (1.5)
TS-81T	NTC	Stainless steel	10 (3)
TCS-J	J-type	Stainless steel	4 (1.21)
TCS-K	K-type	Stainless steel	4 (1.21)

SPECIFICATIONS	
Sensor:	See model chart.
Operating Temperature:	PTC or NTC: -58 to 221°F (-50 to 105°C); J-type: 32 to 1400°F (0 to 760°C); K-type: 32 to 2300°F (0 to 1200°C).
Cable:	PTC and NTC models: PVC; J-type and K-type models: FEP.

ACCESSORIES	
Model	Description
A-TS-AP	1/4 DIN adapter plate
TS-W	Brass thermowell (for use with TS-1, TS-11, TS-2, TS-21)
TS2-K	Configuration key