


PRECISOR® III ELECTRO-PNEUMATIC POSITIONER

Low Cost, Rotary Operation, Selectable Single or Double Action



Proximity **SERIES 275** PRECISOR® III Electro-Pneumatic Positioners combine an easy to use, high performance unit with a low price. Series 275 models accurately control valve stroke of rotary motion valves such as Dwyer Instruments ball or butterfly valves according to an input signal of 4 to 20 mA from the controller. Its rugged, durable design makes it ideal for harsh environments. The NEMA 4X (IP 66) enclosure rating protects the highly efficient microprocessing unit. An analog feedback signal is outputted to stabilize any valve system, and easy to use functions such as auto calibration ensure the accuracy of the Series 275. Low air consumption reduces operating cost, but does not sacrifice the performance of the positioner. The compact design of this unit makes it easy to use with any size actuator. PRECISOR® III Positioners feature user selectable single or double action and LCD screen attached to the outer face of the unit, allowing for an easy inspection of the positioner condition while in the field.

FEATURES/BENEFITS

- Integral LCD for monitoring or programming
- Mounting bracket is included
- Adjustable for various characteristics - quick open or linear valves
- User selectable single or double action

SPECIFICATIONS

Input Signal: 4 to 20 mA DC.
Input Impedance: 460 Ω max @ 20 mA DC.
Enclosure Material: Aluminum diecasting.
Air Supply: 20 to 100 psi (1.4 to 6.9 bar).
Air Connection: 1/4" NPT.
Gage Connection: 1/8" NPT.
Conduit Connection: 1/2" NPT.
Linearity: ±0.5% FS.
Hysteresis: ±0.5% FS.
Sensitivity: ±0.2% FS.
Repeatability: ±0.3% FS.
Air Consumption: Below 0.07 scfm (2 LPM) at 20 psig (1.4 bar) supply.
Flow Capacity: 2.5 scfm (70 LPM) at 20 psig (1.4 bar) supply.
Stroke: 0 to 90°.
Enclosure Rating: IP66.
Temperature Limits: -22 to 185°F (-30 to 85°C).
Lever: NAMUR.
Weight: 3.3 lb (1.5 kg).

MODEL CHART

Model	Communication	Option
275ER-D5000	None	None
275ER-D5001	None	Transmitter
275ER-D5021	HART®	Transmitter